

RS 100c2



Specifications:

Channels	no	2
Class	Typ	AB
Power @14,4V /1.0% THD		
@ 4 ohm stereo:	Wrms	2x 150
@ 2 ohm stereo:	Wrms	2x 230
@ 4 ohm mono:	Wrms	1x 460
Operation supply	V	10 -16
Thermal protection	C	80
THD @ 4 Ω / 50% Pmax	%	0,02
Signal/noise	dB	90
Band width +- 1 dB	Hz	7 -46000
Input sensitivity	Vrms	0,2-8
Low input impedance	Ω	10 k
High input impedance	Ω	33
Damping @ 80 Hz		312
Power consumption, idle	A	0.7
Power cons. 4 Ω stereo	A	31
Power cons. 4 Ω mono	A	56
Power cons. 2 Ω mono	A	N.A.
Weight	kg	3,16
Dimensions	l/w/h	324/180/58 mm

Features:

- Input with low- or high-level signal, RCA output
- High-level with autosense function (no remote signal required)
- Variable switchable Low Pass Filter from 50 to 300 Hz
- Variable switchable High Pass Filter from 25 to 175 Hz
- 12 dB octave crossover slope
- Bass adjust +/- 6 dB (car- resp. woofer-size)
- Optional remote available

Miscellaneous:

- Protection for overhead, over current, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink with intelligent fan cooling